

Designed and
Assembled in
the U.S.A



DOG GUARD
OUT OF SIGHT FENCING

DG9XT Receiver

Features

The DG9XT receiver is designed to handle the “medium-to-stubborn and tough-to-train” dogs. It works well with dogs that are runners such as Huskies, Labs and hunting dogs.

The DG9XT receiver has a low battery light indicator that will let you know that the battery needs to be changed. In addition, this receiver will detect stray signals and also has an indicator light during correction. Thicker case walls provide additional durability.

DG9XT has user friendly red and green LED indicators:

- **Flash red every 8 seconds**—Low battery indicator will alert you to replace the battery.
- **Flash red and green**—During correction for a visual indication that the receiver is working.
- **Flash green rapidly**—Stray signal indicator, if the receiver is in an area where there is a signal that causes the receiver to come out of sleep mode. However, the receiver will not activate.

The receiver is water-resistant provided it was not damaged or abused.

The fail-safe feature shuts the receiver down 30 seconds after it has been activated. The receiver will reset itself

once it has been removed from the signal field for 3 seconds. This feature ensures that your pet will not be continuously stimulated if accidentally caught in the signal field.

The DG9XT receiver provides a pulsating stimulus, so that your Dog Guard professional dealer can adjust the stimulus to match your pet’s temperament.

This receiver can be ordered in the encoded mode or in the non-encoded modes.

The receiver in the encoded mode provides up to 32 levels of initial stimulation that are controlled at the transmitter. When the pet enters the first signal field, it will receive a warning tone or stimulation. Should the pet stray into the second signal zone, the receiver will automatically increase to a stronger stimulus. The maximum stimulus can be controlled by using shunts.

It is available in three frequencies.

Dimensions: 1 3/16" W x 1 1/8" H x 2 1/4" L

Probe Spacing: 1 1/8"

Weight: 2.2 oz.

Your Dog Guard® professional dealer will answer any questions that you have and also help you pick the equipment that is right for you and your pet.

dogguard.com